SCCSID = weir\_specs.man v1.1 02/19/03

Prepared by: Jennifer Barnes

Date: 2/19/03

Hydrologic Systems Modeling Division

\_\_\_\_\_

## | DRAFT DRAFT DRAFT DRAFT DRAFT |

## SOUTH FLORIDA WATER MANAGEMENT MODEL V5.0 INPUT MAN PAGE FOR

\_\_\_\_\_\_

| COLS    | VAR NAME                    | FORMAT     | DESCRIPTION  |
|---------|-----------------------------|------------|--|
| L. NUMI | BER OF PASSIVE WEIRS: (     | 1 record t |  |
| -       | no_of_wiers                 |            | total number of weirs in input file  |
| OF I    |                             | RGE COEFFI | CIENT, EQUATION EXPONENT, CREST HEIGHT, DIRECTION  |
| -       |                             | free       |  |
| -       | irow_wier                   | free       | grid row location of headwater for weir (headwater location must have higher land surface elevation than tailwater location)   |
| -       | dcoef_wier(i)               | free       | discharge coefficient of weir ( = c * weir length  |
| -       | pwr_wier(i)                 | free       | weir exponent used in equation for flow  |
| -       | crstelev_w(i)               | free       | weir crest elevation (feet NGVD), weir crest<br>height must be greater than the land surface<br>elevation at the headwater location  |
| -       | <pre>wier_orient(i,k)</pre> | free       | orientation of weir (direction of flow) options are in order of E W N S D:     where E is eastward (west to east)     where W is westward (east to west)     where N is northward (south to north)     where S is southward (north to south)     where D is diagonal |
| Note:   | Where option is not se      | t a capita | l letter O should be used as a placeholder.  |

| -   | weir_name_wca         | free | name of passive weir or berm (maximum of 6 characters)                        |  |  |  |
|---|-----------------------|------|---|--|--|--|
| -   | icol_weir_tw_constrnt | free | column location of tailwater constraint used to determine when to stop flow   |  |  |  |
| -   | irow_weir_tw_constrnt | free | row location of tailwater constraint used to determine when to stop flow      |  |  |  |
| _   | rmax_tw_stage_wier    | free | stage (feet NGVD) of tailwater constraint used to determine when to stop flow |  |  |  |
|   |                       |      |   |  |  |  |
| END OF DESCRIPTION FOR INPUT FILE "weir_specs.dat" (jabarne 11/20/02) |                       |      |   |  |  |  |
|   |                       |      |   |  |  |  |